



Grease Trap Treatment

PRODUCT INFORMATION SHEET

DESCRIPTION

Ecogreen Grease Trap Treatment is an effective and economical way of dissolving fats, oils, grease and food residue within the grease trap and plumbing system leading to and from the grease trap.

Fats, oils and grease will over time breakdown naturally, but in a busy kitchen environment grease traps aren't given adequate time for this process to occur, allowing grease to accumulate. With weekly or daily application of **Ecogreen Grease Trap Treatment**, the beneficial bacteria used in this product degrade the grease preventing blockages, reducing offensive odours, eliminating drain files and reducing the amount of waste in the grease trap.

With no harsh or hazardous ingredients, **Ecogreen Grease Trap Treatment** can be used in all types of grease traps and plumbing.

Ecogreen Grease Trap Treatment is a simple, clever and environmentally friendly wastewater solution providing a responsible approach to wastewater treatment.

FEATURES & BENEFITS

- Easy to use
- Works instantly
- Contains beneficial bacteria
- Maintains plumbing
- Biodegradable
- Non-toxic, non-corrosive and environmentally friendly

IDEAL FOR USE IN

- Grease Traps
- Plumbing



Grease Trap Treatment

TECHNICAL INFORMATION

DIRECTIONS FOR USE: Shake well before use

This product can either be dosed automatically or manually depending on the requirements. When dosed manually, a predetermined amount of product should be poured down all kitchen drains on a regular basis. When automatically dosed, a specialised unit must be installed and drums changed over as required. Please contact us for further information on dosage rates.

STORAGE

DO NOT mix with detergents and other cleaning products. Store up right, below 30°C and away from direct sunlight.

SAFETY DIRECTIONS

ECOGREEN Grease Trap Treatment is considered non hazardous according to Work Safe Australia and non flammable according to the Australian Dangerous Goods Code. However, inline with safe handling practices, it is recommended that the handling instructions outlined in the Safety Data Sheet and label be followed.

If needed, for advice, contact the Poisons Information Centre (Australia 131 126, NZ 0800 764 766) or contact your local doctor or hospital.

PRODUCT CHARACTERISTICS

Appearance	Yellow Liquid
Scent	Lemon
pH	5-8
Melting Point (°C)	-
Boiling Point (°C)	100
Specific Gravity (20°C)	1.02 ± 0.02
Solubility	Completely Soluble in Water
Flash Point (°C)	Non Flammable

CAUTION:

Avoid contact with eyes
Keep out of reach of children.

FIRST AID:

Eyes - If eye contact occurs, flush thoroughly with water and seek medical advice.

Skin - If signs of swelling, rash or irritation occur on skin, wash area with soap and water and discontinue use.

Swallowed - If swallowed rinse mouth out with water.

Item No.	Description	Size	Carton Qty
C1231	Grease Trap Treatment	10Litre	1
C1248	Grease Trap Treatment	20Litre	1

Information provided in this Technical Data Sheet is correct at the time of printing, however please make sure you read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use and both the label and MSDS contain precautionary statements and first aid procedures. All MSDS are available online at www.ecogreen.com.au or contacting your local sales representative.

**Environmental Technologies
Group P/L**
Head Office
16 Mallett Road
Tullamarine, Victoria, 3043, Australia
Telephone: 1800 000 245

**ETG Environmental Solutions
Sdn Bhd (941086-D)**
No. 16, Jalan Industri USJ 1/9,
Taman Perindustrian USJ 1,
47600 Subang Jaya, Selangor, Malaysia.
Telephone: (+603) 8023 7515

**Environmental Technologies
(Singapore) Pte Ltd**
2 Kaki Bukit Avenue 1 #02-01
Kaki Bukit Industrial Estate
Singapore 417938
Telephone: (+65) 6748 6818